

INSTALLATION INSTRUCTIONS

Item#10315-855

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

HANGING THE FIXTURE (Fig. 1)

1. Carefully remove the fixture from the carton and check that all parts are included as shown in the illustration.
2. Shut off power at the circuit breaker and remove old fixture including the mounting hardware.
3. Thread Decorative Rods (H) into the fixture body (I).
4. Remove mounting screws (F) (Size:#8-32 0.5") from canopy (D). Secure mounting plate (B) to the junction box (not included) using mounting screws (C) (Size:#8-32 1"). The side of the mounting plate marked "GND" must face out.
5. Adjust wire to desired hanging length using the small screw located on the side of wire grip (G) with allen wrench provided.

CONNECTING THE WIRES (Fig. 2)

6. Connect the electrical wires as shown in fig 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate (B) using the green screw provided.
7. Place canopy (D) onto mounting plate (B) and secure with mounting screws (F).

FINISH THE INSTALLATION (Fig. 1)

8. Install (1) one medium base bulb (J) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification—**DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**.


Note: Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.

Your installation is now complete. Return power to the junction box and test the fixture.

Fig1.

1



Set# A-022-120
- Mounting Plate
- Ground Screw
-Mounting Screw*2

Fig. 2

