INSTALLATION INSTRUCTION

Item# 12653-732

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE (Fig.1)

- 1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
- 3. Loosen screws (D) to remove mounting plate (A) from fixture body (C).
- 4. Attach mounting plate (A) to junction box (not included) with mounting screws (B). The side of the mounting plate (A) marked "GND" and two convex points must face out.

CONNECTING THE WIRES (Fig. 2)

- 5. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate (A) using the green screw provided.
- 6. Tuck wire connections neatly inside the junction box.
- 7. Install (2) two candelabra base bulbs (G) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification.—DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PASS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

FINISHING THE INSTALLATION (Fig.1)

- 8. Place fixture body (C) over mounting plate (A) and secure with screws (D).
- 9. Begin from the bottom of the fixture frame, gradually hang the glass(F) to each hook(E) until all the hooks are occupied with glass.

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.





