## INSTALLATION INSTRUCTIONS

Item#15035-XXX

#### **READ AND SAVE THESE INSTRUCTIONS**

# WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

#### AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

## **HANGING THE FIXTURE (Fig. 1)**

- 1. Carefully remove the fixture from the carton and check that all parts are included as shown in the illustration.
- 2. Shut off power at the circuit breaker and remove old fixture including the mounting hardware.
- 3. Remove canopy screws (F) (Size:#8-32 0.5") from canopy (D). Secure mounting plate (B) to the junction box (not included) using mounting screws (C) (Size:#8-32 1"). The side of the mounting plate marked "GND" must face out
- 4. Determine the desired hanging height and thread rods (H, I) to all thread of the fixture body(J). Pass the wires carefully through each rod as you assemble. Then secure the swivel (G) of canopy (D) onto rod (H). Carefully feed the wire through the swivel (G).
- 5. Use the quick connector to connect LED red/black wires to the red/black wires on the driver as shown in Fig.1.
- 6. Use the ring (O) to install the glass (N), glass (P), Then secure glass (Q) onto the thread of socket (K). Do not over tighten.
- 7. The support cable is provided to support the weight of the fixture while wiring. Align the fixture to mounting plate (B) and attach hook (R) on the end of support cable into a slot located on mounting plate (B). Carefully allow the support cable to support the weight of the fixture while wiring.

#### **CONNECTING THE WIRES (Fig. 2)**

- 8. Connect the electrical wires as shown in fig 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate (B) using the green screw provided.
- 9. Tuck the wire connectors neatly into the ceiling junction box.

#### FINISH THE INSTALLATION (Fig. 1)

10. Place canopy (D) onto mounting plate (B) and secure with canopy screws (F).

Note: Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.

Dimmable with ELV and/or LED compatible wall dimmer switches.

Your installation is now complete. Return power to the junction box and test the fixture.





