

INSTALLATION INSTRUCTIONS

Item# 16061-732

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

PREPARATION (Fig. 1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.
3. Loosen mounting screw(D) to remove mounting plate (A) from fixture body(E).
4. Temporarily raise mounting plate (A) to the wall. Mark location for anchors (C), use power drill to drill holes for anchors (C). Insert anchors (C) into hole and press flush with wall. Repeat on opposite side.
5. Screw anchor screws (B) through mounting plate (A) and into anchors (C) (installed in step 4).

COMPLETING THE INSTALLATION (Fig. 1)

6. Placing the fixture body (E) to the wall. Line up the holes in back plate with holes in mounting plate (A) and secure with four mounting screws (D).
7. Screw ceramics shade (H) over the socket (G) by using socket ring (I). Do not over tighten. Adjust arm (F) to proper position.
8. Install (1) one medium base bulb (J) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification. — **DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**.
9. Insert plug into electrical outlet.

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

Fig. 1

Set# A-021-115400

- Mounting Plate*1
- Ground Screw*1
- Mounting Screw*2
- Outlet Box Screw*2

