# INSTALLATION INSTRUCTIONS FOR 2526-732 FOR PENDANT

## READ AND SAVE THESE INSTRUCTIONS

# WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER AVERTISSEMENT!COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DO DISJONCTEU

Fig.1

#### **ASSEMBLING THE FIXTURE (Fig.1)**

- 1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
- Attach the mounting plate (A) to the junction box (not included) using mounting screws (C) (Size: 8-32\*1/2"L). The side of the mounting plate (A) marked "GND" must face out.
- Adjust the cord to reach the height of the fixing device you need and secure with screw (F) (Use the provided hex wrench (I)). To straighten the cord, please use a blow dryer (not included) if necessary.

## **CONNECTING THE WIRES (Fig.2)**

- 5. Connect the electrical wires as shown in Fig.2, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate (A) using the green screw (B) provided.
- 6. Tuck wire connectors neatly into the junction box.

#### **COMPLETING THE INSTALLATION**

- Align the canopy (E) onto the mounting plate (A) and secure with screws (D).
- Install (1) one medium base bulb up to 60 watts each or CFL or LED equivalent (Not included), in accordance with the fixture specification (DO NOT EXCEED THE MAXIMUM WATTAGE RATING!) ( NE PAS DEPASSER LA PUISSNCE NOMINALE MAXIMLE!)
- 9. Rotate the glass (H) to the arm (G). Don't too tighten.

Your installation is now complete. Return power to the junction box and test the fixture.

IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.







