# INSTALLATION INSTRUCTIONS

Item#2890-691 (NEW. 8/18/2021)

READ AND SAVE THESE INSTRUCTIONS

## WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

### AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

#### **PREPARATION (Fig. 1)**

- 1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.

#### ASSEMBLING THE FIXTURE (Fig. 1)

- Determine the desired hanging height by loosening screw (C) from bushing (F) and adjust cord through bushing (F), if necessary, cut cord leaving an additional 8" allowing for electrical connection.
- 4. Secure cord into bushing (F) by tightening screw (C).
- 5. Carefully cut and remove approximately 4" of the outer sheathing from the cord and strip 1/2" of the wire ends bare to expose copper strands.
- Attach mounting plate (A) to junction box (not included) with mounting screws (B) (Size: #8-32N\*L0.5"). The side of the mounting plate (A) marked "GND" and two convex points must face out.

#### **CONNECTING THE WIRES (Fig. 2)**

- 7. Connect the electrical wires as shown in fig 2, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate (A) using the green screw provided.
- 8. Tuck wire connectors neatly into junction box and raise canopy (D) to ceiling.

#### **COMPLETING THE INSTALLATION (Fig. 1)**

- 9. Slide canopy (D) over mounting plate (A) and secure with screws (E).
- 10.Install (1) one candelabra base bulb (H) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification. — DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)
- 11.Screw glass shade (I) onto socket cup (G).

#### 12.

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.





