INSTALLATION INSTRUCTIONS

Item# 3715-788

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER. VERTISEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

ASSEMBLING THE FIXTURE (Fig. 1)

- 1. Shut off ower at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the partrs in a clean area. Ensure not to misplace any small parts necessary for installation.
- 3. To begin assembly of your fixture, first slip fixture loop (J) along the wire and thread onto threaded tube (1) see Fig. 1.

HANGING THE FIXTURE (Fig. 2)

- 4. Thread all thread (D) into collar loop (F) until snug.
- 5. Thread the other end of all thread (D) into crossbar. Note: The lenght of all thread (D) into crossbar maybe adjusted if necessary.
- 6. Use lock washer (B) and hex nut (E3) to secure theaded tube (D) to mounting strap (A).
- Take mounting strap assembly and mount to junction box (JB) *"not provided"* with 8-32 mounting screws (C). The side of crossbar (A) marked with "GND" must be face out.
- 8. Slip canopy (G) and collar ring (I) over quick link (H) and then open quick link (H) and connect to loops (F/J) then close quick link (H).
- 9. Feed fixture wires through collar loop and crossbar assembly.

CONNECTING THE WIRE (Fig. 3)

- 11. Connect the electrical wire as shown in Fig. 3, making sure that all the wire connectors are secured. If your junction box has a ground wire (green, or bare copper), connect fixture's ground wire to it. Otherwise connect fixture's ground wire directly to the crossbar (A) using green screw provided.
- 12. Tuck wire connections neatly into junction box (JB).
- 13. Raise canopy over collar loop (F) and secure with collar ring (I).

FINISHING THE FIXTURE (Fig. 1)

14. Install 9x E12 base bulbs up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

Your installation is now complete. You can now turn the power ON and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.





