

INSTALLATION INSTRUCTION FOR FIXTURE 3723-PL

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE

1. Shut off the power supply at the fuse box or circuit breaker box (avertissement! couper le courant au niveau des fusibles ou du disjoncteur). Remove the old fixture from wall. Including the old cross bar.
 2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to lose any small parts necessary for installation.
 3. Attach the mounting plate (A) to the outlet box using the outlet box screws (B). The side of the mounting plate (A) marked "GND" must face out.
 4. Follow the wiring instructions carefully (See Fig.2).
 5. Attach the fixture back plate (D) over the mounting plate (A) well, and secure with 2 steel screws (C) what are locked by the screw tool (H).
 6. Put the glass shade (G) over the socket (I) and secure it with ring (F) and socket ring (E).
 7. Install the light bulb in accordance with fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING** (ne pas dépasser la puissance nominale maximale!!). The color correlated Temperature (CCT) for replacing the enclosed lamp is (2700K).
 8. This fixture is rated for a minimum start temperature of -17° Celsius.
 9. The ballast and lamp are combined, to replace or install, twist pins into socket as shown on Fig.3.
- Your installation is now complete. Return power to the junction box and test the fixture.

Wiring (See fig.2)

1. Connect the electrical wires as follows. Connect the black wire from the fixture to the black (HOT) house wire. Connect the white wire from the fixture to the white (Neutral) house wire. Make sure all the wire nuts were secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (Green or Bare Copper) connect fixture's ground wire to it. Other wise attach the bare copper fixture wire to the green ground screw on the mounting plate.
2. Tuck the wire connections neatly into the wall junction box.

Fig.2




Fig. 1





Fig.3



Contains Mercury (Hg) Dispose of according to Local, State and Federal Law. (www.epa.gov/bulbrecycling)

