

INSTALLATION INSTRUCTIONS

Item#3811-863

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
VERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

PREPARATION THE FIXTURE

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.
3. Attach the mounting plate (A) to junction box (Not include) using mounting screw (C). The side of the mounting plate (A) marked "GND" must face out.

CONNECTING THE WIRES

4. Connect the electrical wires as shown in Fig.2, making sure that all wire connectors (F) are secured. If your junction box has a ground wire (green or bare copper), connect fixture's ground wire to it. Otherwise, connect fixture's ground wire directly to mounting plate (A) using green screw provided.

COMPLETING THE INSTALLATION

5. Attach backplate (B) to mounting plate (A) and secure with canopy screw (D).
6. Place glass (G1) over threads (J) on frame and secure with plastic washer (W) and decorative knob (K).
7. Secure glass (G2) to threads (J) on pipe (M) using screws (F). Tighten with screwdriver (Not included) as shown in Fig 1. Illustration.
8. Install (1) one candelabra base bulb (J) up to 40 watts or CFL or LED equivalent (not included) in accordance with the fixture's specification. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

