INSTALLATION INSTRUCTIONS

Item#5403-581

READ AND SAVE THESE INSTRUCTIONS

Warning! shut power off at fuse or circuit breaker.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE (Fig. 1)

- 1. Shut off the power at the circuit breaker and remove the old fixture from the ceiling, including the mounting hardware.
- Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
- 3. The Mounting Strap (A) contains several pairs of threaded holes, find the pair of holes that match the holes spacing in your Junction box Attach the Fixture Mounting Strap (A) to the Junction Box using the two mounting screws (B size: 8/32*25mm). Tighten the screws (B) securely with screwdriver.
- 4. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the crossbar using the green screw provided. After wires are connected, tuck them carefully into the outlet box.

CONNECTING THE WIRES (Fig. 2)

 Put the fixture horizontal to match the hole both on the Mounting Strap(A) and fixture body(D) and secure them by threading the screw(C size: 5/32*12mm) tightly.

FINISHING THE INSTALLATION (Fig. 1)

 Install the light bulb(s) (not included) in accordance with the fixture's specifications. (DO NOT EXCEED THE MAXIMUM WATTAGE RATING!). (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

Your installation is now complete. Return power to the outlet box and test the fixture.

Note: Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

MIN 75°C SUPPLY CONDUCTORS







