INSTALLATION INSTRUCTION FOR 6914

For Wall Mount Light Fixtures

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER. AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR

READ AND SAVE THESE INSTRUCTIONS

PREPARATION

- 1. Shut off the power at the fuse box or circuit breaker box. If necessary, remove the old fixture and all mounting hardware from wall junction box.
- 2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to loose any small parts necessary for installation.

MOUNTING THE FIXTURE (FIG.1)

- Position the back plate (A) through the fixing holes onto the wall and make marks, drill pilot holes for wood screws (C) into the wall, then insert the plastic anchors (B) into the holes.
- 4. Secure back plate (A) to outlet box with outlet screws (D), then secure the outlet box with wood screws (C) into plastic anchors (B) in the wall.

CONNECTING THE WIRES (Fig. 2)

- 5. Connect the fixture wires to the junction box wires as shown in Fig. 2. Make sure all wire connectors are secure and do not easily pull off with a slight tug. If there is no green ground wire from the junction box, connect the fixture ground wire to the circular strap or the crossbar with the green screw provided.
- 6. Tuck these wire connections neatly into the wall junction box.

COMPLETING THE INSTALLATION

- Raise the front plate (F) allowing for the mounting screws (E) to protrude through the hole in front plate (F), and secure with the ball nuts (G).
- 8. Install the proper light bulbs specified for your fixture.

(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

- Place the glass panel (I) onto the bottom of the glass frame (K) and the side glass panels (H) into the glass frame (K), then using the sheet metals (L) to compact the glass panels (I, H).
- Place the glass frame (K) over the front plate (F) and then secure it with screws (M) by wrench (N).

Return the power to the junction box and test the fixture. Your installation is now complete.





