INSTALLATION INSTRUCTIONS

For item#72026-A179 (New. 05/08/2019)

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

PREPARATION (Fig.1)

- 1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.

CONNECTING THE WIRES (Fig.2)

- 3. Pull black, white, and ground wires out of post (H).
- 4. Connect electrical wires while supporting the lantern as shown in Fig. 2. If your outlet has a ground wire (green or bare copper), connect the fixture ground wire to it. If not, consult your electrician for proper grounding. After wires are connected, tuck them carefully inside the post. Align the lantern with post and secure with screws (G). (Fig.1&2)

COMPLETING THE INSTALLATION

- 5. For installing bulb, or replacing bulb at a later date, unscrew the screws (D) and remove the top frame (A).
- 6. Install (1) one medium base bulb (C) up to 100 watts or CFL or LED equivalent (not included) in accordance with the fixture specification. (DO NOT EXCEED THE SPECIFIED WATTAGE!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).
- After the installation, align the holes on the top frame (A) with the holes on the fixture body (E) and secure with screws (D).

Your installation is now complete. Return power to the junction box and test the fixture.

<u>Note:</u> Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.



