INSTALLATION INSTRUCTIONS

9836

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE (Fig. 1)

- 1. Shut off power at the circuit breaker and remove old fixture including mounting hardware.
- Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
- 3.Thread all thread (A) into crossbar (B) spaced the same distance apart as the holes in the fixture body(E). Note: The length of all thread (A) into crossbar (B) may be adjusted if necessary.
- Attach the crossbar (B) to outlet box (D) (not supplied) with mounting screws(C). The side of crossbar(B) marked "GND" must face out.

CONNECTING THE WIRES (Fig. 2)

5.Connect the electrical wire as shown in figure 2, making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect the fixture Ground Wire to it. Otherwise, connect the fixture Ground Wire directly to the Crossbar using the Green Screw provided. After wires are connected, tuck them carefully inside the outlet box.

FINISHING THE INSTALLATION (Fig. 1)

6. Place fixture body (E) to crossbar(B),and secure it tightly using Knurled Knobs (F).

7.Install (1) one medium base bulb (G) up to 100 watts or CFL or LED equivalent (not included) in accordance with the fixture specification. (DO NOT EXCEED THE SPECIFIED WATTAGE!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).

8.To prevent moisture from entering the outlet box and causing a short, use clear caulking (ie. Indoor/Outdoor Silicone Sealant) to outline the outside of fixture backplate where it meets the wall leaving a space at bottom to allow moisture a means to escape. (Fig. 3)

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1 and 3) on this manual is for installation









