

©2024 Minka Lighting, LLC. Manual design and all elements of manual design are protected by United States Federal and/or State Law including Patents, Trademark, and/or Copyright Laws.



The Minka-Aire[®] warranty is for one (1) year from the date of purchase from an authorized Minka-Aire[®] dealer. This warranty is only valid to the original purchaser or user against all defects in material and workmanship (light bulbs excluded) for one (1) full year. Additionally, Minka-Aire[®] warrants the motor only for the lifetime of the Minka Aire ceiling fan (excluding wall controls and electrical components), to the original purchaser or user.

•The warranty is voided with the use of any non- Minka-Aire[®] electrical devices, E.g., wall controls or electrical dimmer switches, etc... •The warranty is void once the original purchaser or user ceases to own the fan or the fan is moved from its original point of installation. •The warranty is void with the use of any hanger bracket (non-Minka Aire or non-fan specific) other than the hanger bracket supplied & installed with this specific fan.

Warranty Service Information

To obtain warranty service during the warranty period, the purchaser should return the fan with the sales receipt to the original place of purchase. The authorized Minka-Aire[®] dealer, at its sole discretion, will either repair or replace the fan after verifying the legitimacy of the warranty claim. Replacement is subject to availability of the same model. If the model is unavailable it will be replaced by one of equal value. This is a limited warranty; the original purchaser or user is responsible for the cost of removal and reinstallation of repaired or replacement product.

To obtain the name of the Minka-Aire[®] authorized dealer nearest you call the Minka-Aire[®] customer care department at 1-800-307-3267, or contact Minka-Aire[®] through www.minkagroup.net and select FAQ to answer any questions or if you require additional assistance submit the question form found there.

Data Purchased ______ Store Purchased ______ Model Number _____ F662 _____

CONTENTS

SAFETY RULLES	1	FINISHING THE INSTALLATION	6
PACKAGE CONTENTS	2	ATTACHING THE FAN BLADES	7
INSTALLING THE FAN	3	OPERATING THE REMOTE CONTROL / WALL CONTROL	8
HANGING THE FAN	4	CARE OF YOUR FAN	9
ELECTRICAL CONNECTIONS	5	TROUBLESHOOTING	10
		SPECIFICATIONS	11



1151 Bradford Circle, Corona, CA 92882 • For Customer Assistance Call: 1-800-307-3267



SAFETY RULES

- 1. Before you begin installing the fan, shut power off at the circuit breaker of the fuse box. Also, unplug or disconnect the appliance from the power supply before servicing.
- 2. Be cautious! Read all instructions and safety information before installing your new fan. Review accompanying assembly diagrams.
- 3. Make sure that all electrical connections and the installation comply with the National Electrical Code, ANSI/NFPA 70 and local codes. Hire a qualified electrician or consult a do-it-yourself wiring handbook if you are unfamiliar with installing electrical wiring.
- 4. Make sure the installation site you choose allows the fan blades to rotate without any obstructions. Allow a minimum clearance of 7 feet from the floor and 18 inches from the tip of the blades to the wall.
- 5. If you are mounting the fan to a ceiling fan outlet box, use a U.L. Listed metal octagonal outlet box marked "Acceptable for Fan Support". Secure the box directly to the building structure. The outlet box and its support must be able to support the moving weight of the fan (at least 50 pounds) Do not use a plastic box.
- 6. Caution: To reduce the risk of injury use only the screws provided with the outlet box in conjunction with the lock washers provided with the fan.
- 7. If you are mounting the fan to a joist, make sure it is able to support the moving weight of the fan (at least 50 pounds).
- 8. After you install the fan, make sure that all mounting components are secured to prevent the fan from falling.
- 9. Do not insert anything into the fan blades while the fan is operating.
- 10. Turn the fan off and wait for the blades to stop completely before proceeding with maintenance or cleaning.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care are factors which can not be built into this product. These factors must be supplied by the person (s) installing, caring for and operating the unit.

NOTE: READ AND SAVE ALL INSTRUCTIONS!

WARNING

TO REDUCE THE RISK OF FIRE, ELECTRIC SHOCK OR OTHER PERSONAL INJURY, MOUNT FAN ONLY TO A U.L. LISTED OUTLET BOX OR SUPPORTING SYSTEM MARKED ACCEPTABLE FOR FAN SUPPORT AND USE MOUNTING SCREWS PROVIDED WITH THE OUTLET BOX IN CONJUCTION WITH THE LOCK WASHERS PROVIDED WITH THE FAN. MOST OUTLET BOXES COMMONLY USED FOR FAN SUPPORT OF LIGHTING FIXTURES ARE NOT ACCEPTABLE FOR FAN SUPPORT AND NEED TO BE REPLACED. CONSULT A QUALIFIED ELECTRICIAN IF IN DOUBT.

TO REDUCE THE RISK OF PERSONAL INJURY, DO NOT BEND THE BLADE HOLDERS WHILE INSTALLING, BALANCING THE BLADES OR CLEANING THE FAN. DO NOT INSERT FOREIGN OBJECTS BETWEEN ROTATING FAN BLADES.


TO REDUCE THE RISK OF FIRE OR ELECTRONIC SHOCK, THIS FAN CAN ONLY USE KH968-VAP-60-3 SOLID-STATE SPEED CONTROL WITH RC1000 REMOTE CONTROL ONLY

TO REDUCE THE RISK OF ELECTRIC SHOCK, THIS FAN MUST BE INSTALLED WITH AN ISOLATING WALL CONTROL/SWITCH

PACKAGE CONTENTS

Unpack your fan and check the contents. You should have the following items:

- 1. Hanger bracket
- 2. Canopy
- 3. Canopy cover
- 4. Downrod assembly
- 5. Coupling cover
- 6. Motor assembly
- 7. Fan blades (3)
- 8. Receiver with 5 wire nuts
- 9. Remote control with holder and 2 mounting screws
 10. 1.5V AAA battery (2)
- A. Mounting hardware #10 x 1.5" Wood screws (2 Pcs.) #8 x 3/4" Machine screws (2PCs.) Lock washers (2 PCs.) 4mm Star washers (2 PCs.) Wire nuts (6 PCs.) Washers (2 PCs.)
- B. Blade attachment hardware #1/4" x 35mm Blade screws (7 PCs.)
 Blade countersink (7 PCs.)
- C. Hex wrench D. Balance kit



Tools Required: Philips screw driver, slotted screw driver, step-ladder, wire cutters, electrical tape.


MOUNTING OPTIONS

If there isn't an existing mounting box, then read the following instructions. Disconnect the power by removing fuses or turning off circuit breakers.

Secure the outlet box directly to the building structure. Use appropriate fasteners and building materials. The outlet box and its support must be able to fully support the moving weight of the fan (at least 50 lbs.). Use a UL listed metal outlet box. Do not use a plastic outlet box. Figure 1,2 and 3 are examples of different ways to mount the outlet box.

Note: You may need a longer downrod to maintain proper blade clearance when installing on a a steep, sloped ceiling. Longer downrods are available from your Minka-Aire[®]dealer.

To hang your fan where there is an existing fixture but no ceiling joist, you may need to install a hanger bar as shown in Fig. 4 (available at your Minka Aire[®]dealer).




HANGING THE FAN

WARNING: All of the parts, hardware and components such as the hanger bracket and hanger ball have been provided for your safety and the proper installation of your new ceiling fan. The use of other parts, hardware or components not supplied by Minka Aire[®] with the fan will void the Minka Aire[®] Warranty.


REMEMBER to turn off the power. Follow the steps below to hang your fan properly:

- Step 1. Secure the Hanger Bracket to the ceiling outlet box using the screws provided with your outlet box in conjunction with the lock-washers provided with the fan. (Fig. 5)
 Step 2. Loosen the two Set Screws from the coupling located on the top of the Motor Assembly. (Fig. 6)
- Step 3. Remove the Hitch Pin, Lock Pin and the Hanger Ball from the Downrod Assembly by loosening the Set Screw and removing the Cross Pin. (Fig. 7)



Step 4. Carefully feed fan wires up through the downrod. (Fig. 8) Thread Downrod into the Coupling until the holes are lined up and secure with the Lock Pin and Hitch Pin previously removed, tighten Set Screws. (Fig. 9)

- Step 5. Slip Coupling Cover, Canopy Cover and Canopy onto Downrod. Carefully re-install the Hanger Ball onto the Downrod being sure that it's properly positioned over the Cross Pin and the wires are not twisted, tighten Set Screw. (Fig. 9)
- Step 6. Lift the Motor Assembly and place the Hanger Ball into the Hanger Bracket. Rotate the Motor Assembly as needed until the check groove from the Hanger Ball rests firmly over the registration tab from the Hanger Bracket. Motor Assembly should not rotate if this is done correctly. (Fig. 10)




ELECTRICAL CONNECTIONS

WARNING : The use of Dimming devices not compatible with ceiling fans will cause unwanted behavior including loud humming and will cause permanent damage to you fans electrical component.


WARNING : To avoid possible electrical shock be sure electricity is turned off at the main fuse or breaker box before wiring.

NOTE: The Aire Control[®]System is equipped with a learning frequency function which has 1024 code combinations to prevent potential interference from other remote units. The frequency on your Receiver and Transmitter units have been preset at the factory. (Fig .11) No frequency change is necessary, should you desire to install another fan within the same home or area with a seperate frequency code please see the "frequency interference" troubleshooting section of this instruction manual to learn how to change the frequency.



Step 1. Insert Receiver into Hanger Bracket with the flat side of the Receiver facing the ceiling. (Fig. 12)

Step 2. Motor to Receiver Electrical Connections: Connect the GRAY wire from the fan to the GRAY wire marked "TO MOTOR U" from the Receiver. Connect the RED wire from the fan to the RED wire marked "TO MOTOR V" from the Receiver. Connect the YELLOW wire from the fan to the YELLOW wire marked "TO MOTOR W" from the Receiver. Secure all wire connections with the plastic wire nuts provided. (Fig. 13)




Step 3. Receiver to House Supply Wires Electrical Connections: Connect the WHITE wire (Neutral) from the outlet box to the WHITE wire marked "AC in N" from the receiver. Connect the BLACK wire (Hot) from the outlet box to the BLACK wire marked "AC in L" from the receiver. Secure all wire connections with the plastic wire nuts provided. (Fig. 13)


Step 4. If your outlet box has a GROUND wire (Green or Bare Copper) connect this wire to the Hanger Ball and Hanger Bracket and Receiver Ground wires. If your outlet box does not have a Ground Wire, then connect the Hanger Ball and Hanger Bracket and Receiver Ground Wires together. Secure wire connection with the plastic wire nut provided. (Fig .13)

After making the wire connections, the wires should be spread apart with the grounded conductor and the equipment-grounding conductor on one side of the outlet box and the ungrounded conductor on the other side of the outlet box. Also, the splices after being made should be turned upward and pushed carefully up into the outlet box and make sure there are no loose strands. As an additional precaution we suggest to secure the plastic wire connectors to the wires with electrical tape.

NOTE: Fan must be installed from a maximum distance of 40 feet from the transmitting unit for proper signal transmission between the transmitting unit and the fan's receiving unit.



FINISHING THE INSTALLATION



Step 1. Remove 1 of the 2 screws from the bottom of the hanger bracket and loosen the other one half a turn from the screw head.

Step 2. Slide the canopy up towards the hanger bracket and place the key hole on the canopy over the screw on the hanger bracket, turn canopy until it locks in place at the narrow section of the key holes. (Fig. 14)

Step 3. Align the circular hole on canopy with the remaining hole on the hanger bracket, secure by tightening the two set screws.


NOTE : Adjust the canopy screws as necessary until the canopy and canopy cover are snug.

ATTACHING THE FAN BLADES

Step 1. Align the holes on the blade and the screw holes on the motor. (Fig .15)

Step 2. Use the hex wrench, blade countersinks and the blade screws provided in the hardware pack to install the blades.

NOTE: When install the first blade, do not tighten the blade screws, so the second and third blades can be installed and adjusted easily. Tighten all blade screws after blades are attached in place.



OPERATING THE REMOTE CONTROL / WALL CONTROL

Remote Control only: Install two AAA 1.5 volt batteries (included). To prevent damage to transmitter remove the battery if not used for long periods of time. IMPORTANT : THIS REMOTE CONTROL & DC FAN MOTOR ARE DESIGNED TO PERFORM A ONE TIME SELF CALIBRATION TEST. THIS TEST WILL BEGIN ONCE A NEW CODE HAS BEEN SET, AND WILL LAST APPROXIMATELY ONE MINUTES.

Your DC brushless motor is equipped with a self learning frequency function remote control. Restore power to ceiling fan and test the transmitter as below for proper operation :

A. 1, 2, 3, 4, 5 and 6 button :

These six buttons are used to set the fan speed as follows :

1 = minimum speed4 = medium speed2 = low speed5 = medium high speed3 = medium low speed6 = high speed

B. 🗢 Reverse button :

This button is used to change the direction of the rotation of the blades; forward for warm weather or reverse for cool weather.

C. 📕 button :

This button turns the power Off to the Fan.

D. 💍 button :

These buttons turn the light ON or OFF and also control the brightness settings of the light. The following instructions apply to ceiling fans that feature a DOWN light ($\stackrel{\circ}{\circ}$ button) only or ceiling

fans that feature an UP light (button) and a DOWN light (button) that are controlled independent of each other;

Press and release the button for the desired light to turn the light ON or OFF. Press and hold the button to set the desired light brightness. The light will cycle between bright and dim settings as long as the button is pressed. The light key has an automatic auto-resume feature that allows the light to remain at the same brightness as the last time it was turned off. NOTE : The auto learning function will only mandate within 60 seconds when turning the fan's AC power ON.

. Select desired frequency from the back of transmitter.

2. Within 60 seconds of turning AC power on, press and hold the "I (Off)" button to enter the learning function. Once the fan has detected the remote controls's frequency, the down light of your fan, if applicable, will blink, and the fan blades will start to spin.

NOTE : During self calibration test, the remote will be non-function.

NOTE : The learning frequency function and self calibration test will continue to retain the last set frequency and calibration set even when the AC power is shut off. If the frequency is changed the self calibration test will occur again.

 Lock position: The DC motor has a builtin safety against obstruction during operation. The motor will get locked operation and disconnect power after 30 seconds if interruption occurs. Please remove obstacles before re-set.

2. Over 50W protection: When the receiver detects motor power consumption which is greater than 50W, the receiver's power will stop and operation will be immediately discontinued.Turn the receiver power on after 5 seconds.

Speed settings for warm or cold weather depend on factors such as room size, ceiling height and number of fans.


NOTE : Wait for the fan to stop before reversing the direction of the blade rotation.


Warm Weather (forward)

A DOWNWARD airflow creates a cooling effect as shown in Figure 16. This allows you to set your air conditioner on a warmer setting without affecting your comfort.

Cool Weather (Reverse)

An UPWARD airflow moves warmer air off the ceiling area as shown in Figure 17. This allows you to set your heating unit on a cooler setting without affecting your comfort.





CARE OF YOUR FAN

Here are some suggestions to help maintain your fan.

- Because of the fan's natural movement some connections may become loose. Check the support connections, brackets and blade attachments twice a year. Make sure they are secure. (It is not necessary to remove fan from the ceiling).
- 2. Clean your fan periodically to help maintain its new appearance over the years. Use only a soft brush or lint free cloth to avoid scratching the finish. Plated finishes are sealed with lacquer to minimize discoloration or tarnishing. Do not use water when cleaning, this could damage the motor, wood blades or possibly cause an electrical shock.
- 3. If your fan is provided with wood veneer blades; you can apply a light coat of furniture polish for additional protection and enhanced beauty. Cover small scratches with a light application of shoe polish.

- 4. Use a lint free lightly damp cloth or duster to remove dust from the blades.
- 5. There is no need to oil your fan. The motor has permanently lubricated bearings.
- 6. If your fan is provided with glass shades, clean with lukewarm soapy water and a soft cloth or sponge. DO NOT IMMERSE GLASS SHADES IN HOT WATER. DO NOT PUT GLASS SHADES INTO AN AUTOMATIC DISHWASHER.

WARNING! MAKE SURE THE POWER IS OFF AT THE ELECTRICAL PANEL BOX BEFORE YOU ATTEMPT ANY REPAIRS. REFER TO THE SECTION, "ELECTRICAL CONNECTIONS".

TROUBLESHOOTING

SYMPTOM Fan will not start SOLUTION

- Check to make sure the wall switch is turned on.
- Check circuit fuses or breakers.
- Caution! Make sure the power is turned off before performing the following steps.
- Remove canopy and check wire connections.
- Check wall control transmitter connections (if applicable).
- Note: Fan must be installed at a maximum distance of 40 feet from the transmitting unit for proper signal transmission between the transmitting unit and the fan's receiving unit.

SYMPTOM Fan Sounds Noisy SOLUTION

- Allow a 24-hour "break in" period. Most noises associated with a new fan will go away during this time.
- Make sure the screws that attach the fan blade holder to the motor hub is tight.
- Make sure outlet box is secured to building structure, if necessary use the wood screws provided to further secure outlet box to joist.
- Make sure hanger bracket is secure to the outlet box, screws are tight.

SYMPTOM Fan Wobble

SOLUTION

- NOTE : All blade sets are grouped by weight. Because wood and plastic blades vary in density, the fan may wobble even though blades are matched.
- Make sure outlet box is secured to building structure, if necessary use the wood screws provided to further secure outlet box to joist.
- Make sure hanger bracket is secure to the outlet box, screws are tight.

SYMPTOM Fan / Light Turn On and Off Unexpectedly SOLUTION

• This is caused by interference, Please see "Frequency interference" for steps to change the frequency.

SYMPTOM Frequency Interference SOLUTION

1. Turn the power off to your ceiling fan.

2. Please use a small size tool to change the frequency settings on the control system.

3. Return power to the unit.

Note: After the AC power is on, do not press any other button on the transmitter before pressing the "Stop" button, doing so will cause the procedure to fail.

- 4. Within 60 seconds of turning the Fan's AC power ON. Press the transmitter's "Stop" button and hold the "Stop" button for 10 seconds.
- 5. Once the receiver has detected the set frequency, the down light of your fan if applicable will blink twice. (there is no indication if your fan is not equipped with a light).
- 6. The receiver has now learn the frequency which has been selected on the transmitter. After completing the steps above, you should be able to operate the ceiling fan and light. If the fan is not responding to the transmitter, please turn the power off to the receiver, and repeat the process.

SPECIFICATIONS

These are typical readings. Your actual fan may vary. They do not include amps and wattage used by the light(s).

Fan Size	Speed	Volts	Amps	Watts	RPM	N.W.	G.W.	C.F.
60"	Low High	120 120	0.09 0.76	3.43 47.56	53 174	5.8 kgs	9.4 kgs	3.23´



the DOE approved test method.

* Measure according to

AIRFLOW EFFICIENCY

(CFM/Watt)

572.59

140.10

For any additional information about your Minka Aire[®]Ceiling fan, please write to: 1151 Bradford Circle, Corona, CA 92882 • For Customer Assistance Call: 1-800-307-3267

