

INSTALLATION INSTRUCTIONS

Item#N3509-860

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

PREPARATION (Fig.1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.
3. Attach crossbar to the junction box (not included) with mounting screws (B) (Size: #8-32N*L1/2"). The side of the crossbar (A) with "GND" marked on it and two convex points must face out. The length of nipple (C) into crossbar (A) maybe adjusted if necessary
4. Decide the preferred hanging height and choose the correct length of rods (I, J, K and L) needed. Pass fixture wire up through the rods (I, J, K and L) and fixture loop (F), screw the rods (I, J, K and L) onto all thread (M) of frame (N). Screw fixture loop (F) onto the end of last rod.
5. Slip the collar ring (H) and canopy (G) down over end of rods.
6. Raise the fixture up to the ceiling, then connect the fixture loop (F) to ceiling loop (D) with quick link (E).
7. Feed the wires carefully through the quick link (E), ceiling loop (D) and nipple (C).

CONNECTING THE WIRES (Fig. 2)

8. Connect the electrical wires as shown in Fig 2, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect fixture's ground wire to it. Otherwise, connect fixture's ground wire directly to the crossbar (A) using green screw provided.
9. Tuck wire connectors neatly into the junction box.

COMPLETING THE INSTALLATION (Fig. 1)

10. Carefully raise the canopy (G) up to ceiling, screw with collar ring (H).
11. Install (19) nineteen candelabra base bulbs up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification. — **DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**
12. Screw glass shade (O) onto the frame (N). Do not over tighten.

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

Fig.1

Set #A-012-46B

-Crossbar

-Mounting screws(2)

-Ground screw

Rod#W35-H-860(6")

Rod#W35-1-860(12")





Fig. 2



american
lighting
association