

INSTALLATION INSTRUCTIONS

Item #N6678-274 (12/23/2014)

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

PREPARING THE FIXTURE (Fig.2)

1. Shut off the power at the fuse box or circuit breaker. If necessary, remove the existing fixture and its mounting hardware from the ceiling.
2. Carefully remove the new fixture from the carton and check that all parts are included as shown in the illustration.
3. Thread nipple (K) into the coupling and secure with a hex nut.
4. Place rod (L), cap (M) and frame (F) over nipple (K) and secure with a hex nut.
5. Place frames (E, D and J) onto the arms and secure with screws (Q) as shown.
6. Install the bulbs (H) (4pcs) in accordance with the fixture's specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**
7. Place column (C) over the tube and secure with nut (B).
8. By measuring, determine the desired hanging height and thread rods (A) into the top nipple of the fixture body.
9. Carefully pass the fixture wires and safety cable through each rod (A) as you assemble.
10. Pass the wires through the swivel and canopy (N) and pull tight. Then thread the swivel onto the top of rods (A).

MOUNTING THE FIXTURE (Fig. 1)

IMPORTANT: For a safe and secure installation, this fixture must be installed by means of support that is independent of the outlet box.

SUGGESTED INSTALLATION:

11. Provide a 1/4" IPS pipe with one end securely mounted to a beam or a structural member. The other end should protrude through the center of the outlet box.
12. Attach the hickey to the center 1/4 IPS support pipe.
13. Drill holes on the ceiling in accordance with the holes in the mounting strap and knock the anchor bolt into the holes.
14. Attach the mounting strap to the outlet box using the box screws (Size: #8-32*0.5L) and self-tapping screws. The side of the mounting strap marked "GND" must face out.
15. Lace safety cable through the side of the hickey. Tie off the set screw assembly as shown. Run the cable through the top of the outlet box and secure to a structural member.

CONNECTING THE WIRES (Fig. 3)

16. At this point, connect the electrical wires as shown in Fig. 3, making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting strap using the green screw provided. After the wires are connected, tuck them carefully inside the outlet box.

FINISHING THE INSTALLATION (Fig. 1 & 2)

17. Align the side holes of the canopy (L) to the holes on the side of the mounting plate. Then secure the canopy to the mounting plate using the side screws.
18. Install the bulbs (17pcs) in accordance with the fixture's specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**
19. Install the cup (P) and finial (G) onto the fixture body.

Your installation is now complete. Return power to the outlet box and test the fixture.

Note: Illustration on this manual is for installation purposes only. It may or may not be identical to the fixture purchased. Do not clean your light fixture or parts with water or cleanser.

