## INSTALLATION INSTRUCTIONS

For Model # P1245-L

READ AND SAVE THESE INSTRUCTIONS

## WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

# AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

## PREPARING FOR INSTALLATION (Fig. 1)

- 1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
- 3. Unscrew the screws (G) and separate the mounting plate (B) (Part # A-020-150) from back plate (H).
- Attach the mounting plate (B) to the outlet box (not provided) with the two outlet box screws (C) (Size: 8-32\*1").
  Note: the side of mounting plate marked "GND" must face out.

#### **CONNECTION THE WIRES (Fig. 2)**

5. Connect the electrical wires as shown in (Fig.2), making sure that all wire connectors (D) are secured. If your outlet has a ground wire (green or bare copper), connect the fixture ground wire to it. Otherwise, connect the fixture ground wire directly to the mounting plate using the green screw provided.

#### **FINISHING THE INSTALLATION (Fig.1)**

- 6. Align back plate (H) onto mounting plate (B) and secure with the screws (G).
- 7. To prevent moisture from entering the outlet box and causing shortage, use clear caulking (i.e. Indoor/Outdoor Silicone Sealant) to outline the outside of fixture back-plate where it meets the wall leaving space at bottom to allow moisture a means to escape. (Fig.3)
- 8. Bulb information: (2 x AC LED 3W included)

# DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

Your installation is now complete. Return power to the junction box and test the fixture.

#### Remark:

Fixture cage (I) and panel (F) can be adjusted as Fig.4 showed.





IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.







