

# INSTALLATION INSTRUCTIONS

Item#P1495-712 (New. 10/30/2019)

## READ AND SAVE THESE INSTRUCTIONS

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**

**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

### PREPARATION (Fig. 1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.

### ASSEMBLING THE FIXTURE WITH CHAIN LOOP (Fig. 1&Fig. 2)

3. Slide metal tube (J) to the fixture (L) and secure with screws (K).
4. Determine the desired hanging height and thread rods (F1, F2 and F3) to the threaded nipple (I) attached to the metal tube (J). Then screw loop (H1) to rod (F1). Passing the wires carefully through each rod as you assemble.
5. Attach quick link (G) to loop (H1) and loop (H2) on the canopy (D), carefully feed the wire over loop (H1), quick link (G), and loop (H2).
6. Thread screws (A) into the pre-drilled holes on the circular strap (B) spaced the same distance apart as the holes on the canopy (D).
7. Attach the circular strap (B) to the junction box using mounting screws (C) (Size: #8-32N\*L0.5"). The side of the circular strap marked "GND" must face out.

### CONNECTING THE WIRES (Fig. 3)

8. Connect the electrical wires as shown in fig 3, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the circular strap (B) using the green screw provided.
9. Tuck the wire connectors neatly into the ceiling junction box.

### COMPLETING THE INSTALLATION (Fig. 1)


10. Raise the canopy (D) over screws (A) and secure with decorative nuts (E).
11. Slide the candle covers (O) over the sockets (N) of the fixture body (L).
12. Install (6) six candelabra base bulbs (M) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification—**DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**.

Your installation is now complete. Return power to the junction box and test the fixture.


**Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.**

**Fig. 1**

Set# A-020  
-Circular Strap  
-Ground Screw  
-Mounting Screw\*2




**Fig. 3**



**IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.**


LA-3184E

Fig.2



a. Hardware Bag:

- A. Screw\*2
- B. Circular Strap\*1
- C. Mounting Screw\*2
- D. Canopy \*1
- E. Knurled Knob\*2
- H. Loop\*2
- G. Quick Link\*1



b. Hardware Bag:

- F1. ROD 12"\*1
- F2. ROD 12"\*2
- F3. ROD 6"\*1

