

INSTALLATION INSTRUCTIONS

For Models # P5745-695/084

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE (Fig. 1)

1. Shut off power at the circuit breaker and remove the old fixture including the mounting hardware.
2. Carefully remove the fixture from the carton and check that all parts are included as shown in (Fig 1).
3. Remove mounting screws (G) (Size:# 8-32 0.5") from canopy (C). Secure mounting bracket (H) to the outlet box (Not included) using mounting screws (F) (Size:#8-32 1"). The side of mounting bracket (H) marked "GND" must face out.

SUGGESTED INSTALLATION (Fig. 1)

4. Determine desired hanging height and thread rods (A,B) to fixture body (D). Use all thread(s) (N) to connect multiple rods. Pass wire carefully through each rod as you assemble. Take off all thread(s) (N) if you only use one rod.
5. Slide canopy (C) on rods (A) or (B), then thread hanger ball (O) to rods.
6. While holding fixture, install it into mounting bracket (H) by tilting at a slight angle so the hanger ball (O) slips into mounting bracket (H). Align the notch in hanger ball (O) to tab on mounting bracket (H) to prevent fixture from turning.

CONNECTING THE WIRES (Fig. 2)

7. Connect electrical wires as shown in Fig. 2, making sure that all wire connectors (E) are secured. If your outlet box has a ground wire (green or bare copper), connect it to mounting bracket (H). Otherwise, connect the ground wire from hanger ball (O) directly to mounting bracket (H) ground wire and secure with wire connectors provided.

FINISHING THE INSTALLATION (Fig. 1)

8. Align canopy (C) over mounting bracket (H) and secure with mounting screws (G).
9. Install medium base bulbs (I) up to 75 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification—**DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**.
10. Align small white metal washer (J), plastic washer (X) and glass diffuser (K) to bottom center stem of fixture body (D).
11. Use plastic washer (X), large white metal washer (L) and cap (M) to secure glass diffuser (K) to fixture body (D).
- 12.

Your installation is now complete. Return power to the outlet box and test the fixture.

IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.

