



MEASUREMENTS

Blade Finish:	
Blade Material:	PLYWOOD WITH PAPER OVERLAY
Blade Sweep:	52"
No. of Blades:	5
Blade Pitch:	12 DEGREES
Reversible Blades:	NO
Slope:	YES
Hanging Weight:	14.48
Downrod 1:	6
Downrod 1 Outside Dia:	0.75
Downroad 2:	
Downrod 2 Outside Dia:	
Ceiling to Lowest Point: (Dim A):	12.25
Ceiling to Blade (Dim B):	10.5
Lead Wire:	80 INCH
Power:	AC
Motor Size:	AC 153 X 15 MM

	Low	Low/Med.	Medium	Med/High	High
RPM	72				196
Amps	0.22				0.57
Watts	10.54				67.5
CFM	1746.0				5450.0
CFM/Watts	165.65				80.74

LAMPING

No. of Bulbs:	0	
Max Bulb Wattage:		
Light Type:		
Light Kit Optional:	NO	
Socket:		
Integrated Light Kit:	NO	
Dimmable:	NO	
Ballast:		
Rated Life Hours:		
Uplight:	NO	
Bulb/LED Included:		
Color Temp.:		
CRI:		
Initial Lumens:		
Delivered Lumens:		

Contractor - 52" Ceiling Fan

Item #:	F556-BNK
UPC Code:	706411061905
Product Family Name:	Contractor Plus
Finish:	Burnished Nickel
Category:	INTERIOR FAN
Category Type:	Ceiling Fan
Certification:	4000048
Patents:	
Notes:	



ETL Intertek

GLASS

Description:			
Material:			
Part No.:			
Quantity:			
Width:			
Height:			
Lenath:			

CONTROLS

Pull Chain Control:	YES
Works with Remote Control:	YES
Works with Wall Control:	YES
Reversible:	NO
Included Remote Control:	
Included Wall Control:	
Smart Control:	NO
Compatible Remote Control(s):	RCS223
Compatible Wall Control(s):	WC106-WH,WCS223,WSC213
Compatible Smart Control:	

SHIPPING

Carton Width:	12.5	
Carton Height:	9.25	
Carton Length:	22.0	
Carton Weight:	17.25	
Carton Cubic Feet:	1.472	
Small Package Shippable:	YES	
Master Pack Width:		
Master Pack Height:		
Master Pack Length:		
Master Pack Weight:		
Master Cubic Feet:		
Multi-Pack:	1	
Master Pack:	1	

MaRNING: Handling this product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. Wash hands with soap and water after installing, handling, cleaning or otherwise bushing his product for more information go to www.P6SWarnings.ca.gov.

For additional information, please contact Customer Care:1-800-221-7977 | Product depicted on this specisheet is protected by United States Federal and/or State laws including US Patent Trademark and/or Copyright and unfair competition laws. Unauthorized reproduction or use carries severe legal penalities.

Rev03.14.202512:35 PM