



MEASUREMENTS

Blade Finish:	
Blade Material:	ABS
Blade Sweep:	60"
No. of Blades:	3
Blade Pitch:	VARIABLE
Reversible Blades:	YES
Slope:	YES
Hanging Weight:	13.89
Downrod 1:	6
Downrod 1 Outside Dia:	.75
Downroad 2:	
Downrod 2 Outside Dia:	
Ceiling to Lowest Point: (Dim A):	16.0
Ceiling to Blade (Dim B):	15.25
Lead Wire:	80"
Power:	DC
Motor Size:	DC 120 X20 MM

	Low	Low/Med.	Medium	Med/High	High
RPM	74				169
Amps	0.08				0.563
Watts	4.55				39.9
CFM	2974.0				7652.0
CFM/Watts	653.63				191.78

LAMPING

No. of Bulbs:	1
Max Bulb Wattage:	15
Light Type:	LED
Light Kit Optional:	NO
Socket:	LED MODULE
Integrated Light Kit:	YES
Dimmable:	YES
Ballast:	
Rated Life Hours:	30000
Uplight:	NO
Bulb/LED Included:	YES
Color Temp.:	3000
CRI:	92
Initial Lumens:	1127.0
Delivered Lumens:	1010.0

Tear - LED 60" Ceiling Fan

Item #:	F831L-ORB
UPC Code:	706411058660
Product Family Name:	Tear
Finish:	Oil Rubbed Bronze
Category:	INTERIOR FAN
Category Type:	Ceiling Fan
Certification:	3064964
Patents:	
Notes:	







mpatible

GLASS

Description:	ETCHED WHITE
Material:	GLASS
Part No.:	
Quantity:	1
Width:	
Height:	
Length:	

CONTROLS

Pull Chain Control:	NO
Works with Remote Control:	YES
Works with Wall Control:	YES
Reversible:	YES
Included Remote Control:	RC500
Included Wall Control:	
Smart Control:	NO
Compatible Remote Control(s):	
Compatible Wall Control(s):	WC500
Compatible Smart Control:	BD-1000

SHIPPING

Carton Width:	13.38
Carton Height:	11.75
Carton Length:	36.5
Carton Weight:	18.26
Carton Cubic Feet:	3.321
Small Package Shippable:	YES
Master Pack Width:	
Master Pack Height:	
Master Pack Length:	
Master Pack Weight:	
Master Cubic Feet:	
Multi-Pack:	1
Master Pack:	1

MaRNING: Handling this product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. Wash hands with soap and water after installing, handling, cleaning or otherwise bushing his product for more information go to view. P65Warnings.ca.gov.

For additional information, please contact Customer Care: 1-800-221-7977 | Product depicted on this specisheet is protected by United States Federal and/or State laws including US Patent, Trademark and/or Copyright and unfair competition I away. Unauthorized reproduction or use carries severe legal penalties.