minkaAire.



MEASUREMENTS

Blade Finish:	
Blade Material:	ABS
Blade Sweep:	54"
No. of Blades:	5
Blade Pitch:	14 DEGREES
Reversible Blades:	NO
Slope:	YES
Hanging Weight:	13.47
Downrod 1:	6
Downrod 1 Outside Dia:	.75
Downroad 2:	
Downrod 2 Outside Dia:	
Ceiling to Lowest Point: (Dim A):	13.75
Ceiling to Blade (Dim B):	11.5
Lead Wire:	8" (EXTENDING WIRES 18"+24")
Power:	DC
Motor Size:	DC 123 X 30 MM

ſ		Low	Low/Med.	Medium	Med/High	High
	RPM	102				169
	Amps	0.07				0.58
	Watts	4.44				46.7
	CFM	2563.0				8385.0
	CFM/Watts	577.25				179.55

LAMPING

No. of Bulbs:	1
Max Bulb Wattage:	20
Light Type:	Z04 LED
Light Kit Optional:	NO
Socket:	Y06 LED MODULE
Integrated Light Kit:	YES
Dimmable:	YES
Ballast:	
Rated Life Hours:	30000
Uplight:	NO
Bulb/LED Included:	YES
Color Temp.:	3000
CRI:	97
Initial Lumens:	1647.2
Delivered Lumens:	1080.9

Cone - LED 54" Ceiling Fan

Item #:	F541L-ORB
UPC Code:	706411058745
Product Family Name:	Cone
Finish:	Oil Rubbed Bronze with
	Medium Maple Blades
Category:	EXTERIOR FAN
Category Type:	Ceiling Fan
Certification:	4009339
Patents:	U.S. Patent(s): D851,232;
rdlents.	D940,851

Notes:





GLASS

Description:	WHITE	
Material:	GLASS	
Part No.:		
Quantity:	1	
Width:		
Height:		
Length:		

CONTROLS

NO
YES
YES
YES
RC400
NO
WC400
BD-1000

SHIPPING

Carton Width:	11.25
Carton Height:	9.75
Carton Length:	27.13
Carton Weight:	15.97
Carton Cubic Feet:	1.722
Small Package Shippable:	YES
Master Pack Width:	
Master Pack Height:	
Master Pack Length:	
Master Pack Weight:	
Master Cubic Feet:	
Multi-Pack:	1
Master Pack:	1

WMNING: Islanding this production request you to chemiskal including lead which is known the Sate of California to
ansis cancer and the disktore of the reproduction fam. Which handwork subs and which the fam.
Weak and which a set of the reproduction of the reproduction of the reproduction of the reproduction.
For additional information, please control Culstomer Care:-1800-221:7977) Product depicted on this spec sheets
production of the reproduction of use anries severe legal periodes.
RevOil E2024 1016 AM
RevOil E2024 1016 AM